



Easily Configured to Meet Your Needs:

PLATFORM OPTIONS

- Standard platform
- Sliding mid-rail extension deck
- Gated extension deck
- Stock Picker platform
- Stock Picker platform with adjustable tray
- Stock Picker platform with rear parcel tray
- Standard AWP platform
- Narrow AWP platform
- Standard fiberglass platform
- Narrow fiberglass platform

POWER OPTION

- 24 V (4- 6 V 225 Ah batteries)

TIRE OPTION

- Non-marking tire

Standard Features

MEASUREMENTS:

- GR™-15 has 20 ft 8 in (6.47 m) working height
- GR™-15 has 14 ft 8 in (4.47 m) platform height
- Up to 500 lb (227 kg) lift capacity

POWER:

- Automatic 25 amp battery charger

PRODUCTIVITY:

- Patented rigid mast system
- Compact base 29.5 x 53 in (75 cm x 1.35 m)
- Standard sliding-midrail platform- 29.5 x 35 in (75 x 88 cm)
- Low 15 in (38 cm) platform entry height
- Adjustable work station tray
- Fully proportional lift and drive controls
- On-board diagnostic system
- AC power to platform
- Descent and tilt alarm
- Auxiliary platform lowering
- Zero inside turning radius
- Dual wheel brakes
- Hydraulic brake release
- Pothole protection
- Hinged rear covers for easy access to all major electrical and hydraulic components
- Large forklift pockets 2.5 x 5.125 in (6.4 x 13 cm)
- Tie down attachment points
- Non-marking tires

Options and Accessories

PRODUCTIVITY

- Sliding mid-rail extension deck
- Gated extension deck
- Stock Picker platform with adjustable tray
- Stock Picker rear parcel tray
- Stock Picker bike rack
- Standard AWP platform
- Narrow AWP platform
- Standard fiberglass platform
- Narrow fiberglass platform
- Fluorescent tube caddy
- Motion alarm and flashing beacons
- Automotive horn

POWER:

- 800 watt inverter (120-230 V AC 50-60 Hz)
- Maintenance-free batteries