


AERIAL WORK PLATFORMS

IWP™ -20S -25S -30S

Specifications

MODELS	IWP™-20S		IWP™-25S		IWP™-30S	
MEASUREMENTS	US	Metric	US	Metric	US	Metric
Working height*	26 ft 5 in	8.22 m	30 ft 5 in	9.44 m	35 ft 6 in	11 m
Platform height	20 ft 5 in	6.22 m	24 ft 5 in	7.44 m	29 ft 6 in	9 m
A Horizontal outreach**	2 ft 2 in	.66 m	—	—	—	—
B Height - stowed:						
fully lowered	6 ft 4 in	1.93 m	6 ft 4 in	1.93 m	6 ft 4 in	1.93 m
base raised	6 ft 6 in	1.98 m	6 ft 6 in	1.98 m	6 ft 6 in	1.98 m
C Length	5 ft	1.52 m	5 ft	1.52 m	5 ft	1.52 m
D Width - standard base	2 ft 8 in	.81 m	2 ft 8 in	.81 m	—	—
wide base	3 ft 4 in	1.02 m	3 ft 4 in	1.02 m	3 ft 4 in	1.02 m
Corner access***	6 in	.15 m	6 in	.15 m	7 in	.18 m



PRODUCTIVITY						
Lift capacity: ANSI/CE	350 lbs	159 kg	350 lbs	159 kg	350 lbs	159 kg
CSA	300 lbs	136 kg	300 lbs	136 kg	—	—
With outreach option	300 lbs	136 kg	—	—	—	—
Platform Dimensions (l/w/h) E/F/G						
Standard	27/26/44.75 in	69/66/114 cm	27/26/44.75 in	69/66/114 cm	27/26/44.75 in	69/66/114 cm
Gated standard	27/26/44.75 in	69/66/114 cm	27/26/44.75 in	69/66/114 cm	27/26/44.75 in	69/66/114 cm
Gated ultra narrow**	22/18/44.75 in	56/46/114 cm	22/18/44.75 in	56/46/114 cm	22/18/44.75 in	56/46/114 cm
Gated narrow	26/20/44.75 in	66/51/114 cm	26/20/44.75 in	66/51/114 cm	26/20/44.75 in	66/51/114 cm
Front entry gated narrow	20/26/44.75 in	51/66/114 cm	20/26/44.75 in	51/66/114 cm	20/26/44.75 in	51/66/114 cm
Front/side entry extra-large**	30/28/44.75 in	76/71/114 cm	30/28/44.75 in	76/71/114 cm	30/28/44.75 in	76/71/114 cm
Standard fiberglass**	29/26.5/43.5 in	74/67/110 cm	29/26.5/43.5 in	74/67/110 cm	29/26.5/43.5 in	74/67/110 cm
Narrow fiberglass**	26/22/43.5 in	66/56/110 cm	26/22/43.5 in	66/56/110 cm	26/22/43.5 in	66/56/110 cm

POWER	
AC models	110 V / 50-60 Hz or 220 V / 50-60 Hz
DC models	12V / 110 V / 60 Hz or 110/230 Hz worldwide model

WEIGHT****						
Standard base						
ANSI (AC)	1,028 lbs	466 kg	1,331 lbs	604 kg	—	—
ANSI (DC)	1,112 lbs	504 kg	1,415 lbs	642 kg	—	—
CE (AC)	1,283 lbs	582 kg	1,331 lbs	604 kg	—	—
CE (DC)	1,367 lbs	620 kg	1,415 lbs	642 kg	—	—
Standard base with outreach option						
ANSI (AC)	1,348 lbs	611 kg	—	—	—	—
ANSI (DC)	1,432 lbs	650 kg	—	—	—	—
CE (AC)	1,384 lbs	611 kg	—	—	—	—
CE (DC)	1,432 lbs	650 kg	—	—	—	—
Wide base						
ANSI (AC)	1,086 lbs	493 kg	1,134 lbs	514 kg	1,146 lbs	520 kg
ANSI (DC)	1,170 lbs	531 kg	1,218 lbs	552 kg	1,362 lbs	618 kg
CE (AC)	1,283 lbs	582 kg	1,114 lbs	505 kg	1,146 lbs	520 kg
CE (DC)	1,367 lbs	620 kg	1,198 lbs	543 kg	1,362 lbs	618 kg
CSA (AC)	1,266 lbs	574 kg	1,644 lbs	746 kg	—	—
CSA (DC)	1,350 lbs	612 kg	1,728 lbs	784 kg	—	—
Wide base with outreach option						
ANSI (AC)	1,199 lbs	544 kg	—	—	—	—
ANSI (DC)	1,283 lbs	582 kg	—	—	—	—
CE (AC)	1,384 lbs	611 kg	—	—	—	—
CE (DC)	1,432 lbs	650 kg	—	—	—	—
CSA (AC)	1,331 lbs	604 kg	—	—	—	—
CSA (DC)	1,415 lbs	642 kg	—	—	—	—

STANDARDS COMPLIANCE	ANSI A92.3, CSA B354.1, CE Compliance, AS 1418.10
----------------------	---

* The metric equivalent of working height adds 2 m to platform height. U.S. adds 6 ft to platform height.

** Gated ultra narrow, front and side entry extra-large, and fiberglass platforms are not available with the outreach option.

*** Corner of platform top rail to corner of wall with ability to rotate leveling jack handle.

**** Weight will vary depending on options and/or country standards.

Features

EASILY CONFIGURED TO MEET YOUR NEEDS

PLATFORM OPTIONS

- Sliding mid-rail standard platform
- Gated standard platform
- Gated ultra narrow platform
- Gated narrow platform
- Standard fiberglass platform
- Narrow fiberglass platform

POWER OPTIONS

- AC power 110 V / 50-60 Hz
- AC power 220 V / 50-60 Hz
- DC power 110 V / 50-60 Hz
- DC power 110/230 Hz worldwide
- Power assist option

BASE OPTIONS

- Standard base (IWP™-20S and 25S only)
- Wide base

STANDARD FEATURES

MEASUREMENTS

IWP™-20S

- 26 ft 5 in (8.22 m) working height
- 20 ft 5 in (6.22 m) platform height
- 2 ft 8 in (.81 m) standard base width
- 3 ft 4 in (1.02 m) wide base width
- Outreach option adds 2 ft 2 in (.66 m) of horizontal reach
- Up to 350 lb (159 kg) lift capacity

IWP™-25S

- 30 ft 5 in (9.44 m) working height
- 24 ft 5 in (7.44 m) platform height
- 2 ft 8 in (.81 m) standard base width
- 3 ft 4 in (1.02 m) wide base width
- Up to 350 lb (159 kg) lift capacity

IWP™-30S

- 35 ft 6 in (11 m) working height
- 29 ft 6 in (9 m) platform height
- 3 ft 4 in (1.02 m) wide base width
- Up to 350 lb (159 kg) lift capacity

PRODUCTIVITY

- Sliding mid-rail platform
- AC power to platform
- Auxiliary platform lowering
- Dual activated up/down switch
- Ground fault interrupt power receptacle
- Most rigid mast in the industry
- Built-in level sensing with interlocks
- Choose from standard or wide base
- Standard base rolls through standard doorways
- Wide base rolls through double doorways
- Overhead crane attachment points
- Wide forklift pockets
- Tie down attachment points

POWER

- AC power 110 V / 50-60 Hz
- AC power 220 V / 50-60 Hz
- DC power 110 V / 50-60 Hz
- DC power 110/230 Hz worldwide



OPTIONS & ACCESSORIES

PRODUCTIVITY

- Outreach option (IWP™-20S only)
- Platform locating laser light
- Tool tray
- Fluorescent tube caddy
- Operational warning light and descent alarm package
- Gated standard platform
- Gated ultra narrow platform (not available with outreach)
- Gated narrow platform
- Standard fiberglass platform (not available with outreach)
- Narrow fiberglass platform (not available with outreach)

POWER

- Power wheel assist with dual battery package
- Dual battery package

Continuous improvement of our products is a policy. Product specifications are subject to change without notice or obligation. Photographs and drawings in this brochure are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on the proper use of this equipment. Failure to follow the appropriate Operator's Manual when using our equipment or to otherwise act irresponsibly may result in serious injury or death. Prices and specifications subject to change without notice. The only warranty applicable is the standard written warranty applicable to the particular product and sale. No other warranty, expressed or implied.