


## Specifications

MODELS	DPL™-25S		DPL™-30S		DPL™-35S	
MEASUREMENTS	US	Metric	US	Metric	US	Metric
Working height*	31 ft 4 in	9.70 m	36 ft	11.14 m	40 ft 9 in	12.06 m
Platform height	25 ft 4 in	7.70 m	30 ft	9.14 m	34 ft 9 in	10.06 m
Height - stowed	6 ft 6 in	1.98 m	6 ft 6 in	1.98 m	6 ft 6 in	1.98 m
Length - stowed	6 ft 9.75 in	2.08 m	6 ft 9.75 in	2.08 m	6 ft 9.75 in	2.08 m
Width	2 ft 7.5 in	.80 m	2 ft 7.5 in	.80 m	2 ft 7.5 in	.80 m



PRODUCTIVITY							
Lift capacity:	ANSI (Domestic)	750 lbs	340 kg	750 lbs	340 kg	600 lbs	272 kg
	CE (European)	750 lbs	340 kg	750 lbs	340 kg	600 lbs	272 kg
	CSA (Canadian)	600 lbs	272 kg	600 lbs	272 kg	500 lbs	227 kg

ANSI							
Outrigger footprint:							
A length	6 ft 10 in	2.08 m	7 ft 2.25 in	2.19 m	7 ft 2.25 in	2.19 m	
B width	4 ft 8.5 in	1.44 m	5 ft 8.75 in	1.75 m	5 ft 8.75 in	1.75 m	
C corner access	1 ft 5 in	.43 m	2 ft	.61 m	2 ft	.61 m	
D wall access front	7 in	.18 m	9 in	.23 m	9 in	.23 m	
E wall access side	1 ft 4 in	.41 m	1 ft 10 in	.56 m	1 ft 10 in	.56 m	

CSA							
Outrigger footprint:							
A length	7 ft 5 in	2.26 m	7 ft 9 in	2.36 m	7 ft 9 in	2.36 m	
B width	6 ft 4.25 in	1.94 m	7 ft 2 in	2.18 m	7 ft 2 in	2.18 m	
C corner access	2 ft 5 in	.74 m	2 ft 10 in	.86 m	2 ft 10 in	.86 m	
D wall access front	11 in	.28 m	1 ft 1 in	.33 m	1 ft 1 in	.33 m	
E wall access side	2 ft 3 in	.69 m	2 ft 7 in	.79 m	2 ft 7 in	.79 m	

CE							
Outrigger footprint:							
A length	6 ft 10 in	2.08 m	7 ft 2.25 in	2.19 m	7 ft 2.25 in	2.19 m	
B width	4 ft 8.5 in	1.44 m	5 ft 8.75 in	1.75 m	5 ft 8.75 in	1.75 m	
C corner access	1 ft 5 in	.43 m	2 ft	.61 m	2 ft	.61 m	
D wall access front	7 in	.18 m	9 in	.23 m	9 in	.23 m	
E wall access side	1 ft 4 in	.41 m	1 ft 10 in	.56 m	1 ft 10 in	.56 m	

Platform length	6 ft	1.83 m	6 ft	1.83 m	6 ft	1.83 m
Platform width	2 ft 3.5 in	.70 m	2 ft 3.5 in	.70 m	2 ft 3.5 in	.70 m

POWER	
Power source: AC models	110 V / 50-60 Hz or 220 V / 50-60 Hz
DC models	12 V

WEIGHT**						
AC	1,375 lbs	624 kg	1,475 lbs	669 kg	1,575 lbs	714 kg
DC	1,450 lbs	658 kg	1,550 lbs	703 kg	1,650 lbs	748 kg

STANDARDS COMPLIANCE	ANSI A92.3, CSA B354.1, CE Compliance, AS 1418.10
----------------------	---

\* The metric equivalent of working height adds 2 m to platform height. U.S. adds 6 ft to platform height.

\*\* Weight will vary depending on options and/or country standards

## Features

### EASILY CONFIGURED TO MEET YOUR NEEDS

#### PLATFORM

- 6 ft x 2 ft 3.5 in (1.83 m x .70 m) platform

#### POWER OPTIONS

- AC power 110 V / 50-60 Hz
- AC power 220 V / 50-60 Hz
- DC power 12 V 190 amp battery

### STANDARD FEATURES

#### MEASUREMENTS

##### DPL™-25S

- 31 ft 4 in (9.70 m) working height
- 25 ft 4 in (7.70 m) platform height
- 2 ft 7.5 in (.80 m) base width
- 600-750 lb (272-340 kg) lift capacity

##### DPL™-30S

- 36 ft (11.14 m) working height
- 30 ft (9.14 m) platform height
- 2 ft 7.5 in (.80 m) base width
- 600-750 lb (272-340 kg) lift capacity

##### DPL™-35S

- 40 ft 9 in (12.06 m) working height
- 34 ft 9 in (10.06 m) platform height
- 2 ft 7.5 in (.80 m) base width
- 500-600 lb (227-272 kg) lift capacity

#### PRODUCTIVITY

- Large platform with room for 1-2 workers
- AC power to platform
- Auxiliary platform lowering
- Dual activated up/down switch
- Ground fault interrupt power receptacle
- Most rigid mast in the industry
- Durable base system
- Angled entry ladder
- LED lights confirm proper setup of outriggers
- Patented outrigger interlock system
- Swivel-lock casters
- Easily rolls through standard doorways
- Outrigger storage pockets
- Multi-direction forklift pocket access
- Winch attachment points
- Tie down attachment points
- Locking key switch

#### POWER

- DC models include a 15 amp charging system with 110 V / 50-60 Hz or 220 V / 50-60 Hz input voltages



### OPTIONS & ACCESSORIES

#### PRODUCTIVITY

- Platform locating laser light
- Tool tray
- Fluorescent tube caddy
- Operational warning light and descent alarm package

#### POWER

- AC power 110 V / 50-60 Hz
- AC power 220 V / 50-60 Hz
- DC power 12 V 190 Amp battery