

Trailer Scissor Lift

UpRight
POWERED ACCESS



- Working height up to 9.0m
- Auto-levelling outriggers with load limiting device
- 2 person lift capacity
- Roll-out deck extension

XT24AL

XT24AL trailer scissor lift specifications

	XT24AL
max. working height	9.0m
max. platform height A	7.0m
platform capacity (SWL)	227kg
outrigger footprint	2.0m x 1.75m
guardrail height B	1.10m
platform size (deck extended)	1.2m x 2.43m
deck extension C	0.81m
stowed height D	2.26m
towing width E	1.54m
towing length F	3.22m
gross weight	1160kg
control system	Electric Push Button
power source	24v DC Deep Cycle Battery

Specifications subject to change without notice. Photos and diagrams in this brochure are for promotional purposes only. Refer to appropriate UpRight Operators manual for detailed instructions on the proper use and maintenance.



Quick and easy to set up - outriggers pull out and lock into place. One button to autolevel the machine

standard features

- Auto-levelling outriggers with load limiting device
- On board battery charger
- Removable guardrails
- Tilt alarm
- Non-slip platform and extension deck
- Two person platform
- Overload alarm
- 1 year parts and labour warranty

options

- Tool tray
- Power to platform
- Spare tyre
- Narrow jacking option with reduced working height

skyreach
access solutions

Sky House, Daurada Drive, Stafford,
Staffordshire, ST17 4XW, U.K.

Tel: + 44 (0) 1785 244177 Fax: + 44 (0) 1785 229874

www.skyreachaccess.com