


Specifications



MODELS	GL™-4		GL™-8		GL™-10		GL™-12	
MEASUREMENTS	US	Metric	US	Metric	US	Metric	US	Metric
A Height - stowed ^{1,2,3}	5 ft 7.5 in	1.72 m	5 ft 7.5 in	1.72 m	6 ft 5.5 in	1.97 m	7 ft 6.75 in	2.31 m
max forks up	5 ft 11 in	1.80 m	10 ft .5 in	3.06 m	11 ft 8 in	3.56 m	13 ft 9.5 in	4.20 m
max forks down	4 ft 1.5 in	1.26 m	8 ft 3 in	2.51 m	9 ft 10.5 in	3.01 m	12 ft	3.66 m
min forks down	3.5 in	.09 m	3.5 in	.09 m	2 in	.05 m	2 in	.05 m
STANDARD BASE								
B Length - stowed	1 ft	.30 m	1 ft	.30 m	—	—	—	—
operating	2 ft 10.75 in	.88 m	2 ft 10.75 in	.88 m	—	—	—	—
C Width: outside	2 ft .75 in	.63 m	2 ft .75 in	.63 m	—	—	—	—
Weight - standard caster options	113 lbs	51 kg	132 lbs	60 kg	—	—	—	—
pneumatic caster options	117 lbs	53 kg	136 lbs	62 kg	—	—	—	—
STRADDLE BASE								
Length - stowed	1 ft 7.25 in	.49 m	1 ft 7.25 in	.49 m	1 ft 7.25 in	.49 m	1 ft 7.25 in	.49 m
operating	3 ft 7 in	1.09 m	3 ft 7 in	1.09 m	3 ft 7 in	1.09 m	3 ft 7 in	1.09 m
Width - stowed ⁴	2 ft 4.75 in	.73 m	2 ft 4.75 in	.73 m	2 ft 4.75 in	.73 m	2 ft 4.75 in	.73 m
max ⁴	3 ft 7.5 in	1.10 m	3 ft 7.5 in	1.10 m	3 ft 7.5 in	1.10 m	3 ft 7.5 in	1.10 m
max inside	3 ft	.91 m	3 ft	.91 m	3 ft	.91 m	3 ft	.91 m
Weight - standard caster options	126 lbs	57 kg	145 lbs	66 kg	149 lbs	68 kg	154 lbs	70 kg
pneumatic caster options	130 lbs	59 kg	149 lbs	68 kg	153 lbs	69 kg	158 lbs	72 kg
4-point caster option A	137 lbs	62 kg	156 lbs	71 kg	160 lbs	73 kg	165 lbs	75 kg
4-point caster option B	139 lbs	63 kg	158 lbs	72 kg	162 lbs	73 kg	167 lbs	76 kg
COUNTERWEIGHT BASE								
Length - operating	2 ft 4.5 in	.72 m	2 ft 4.5 in	.72 m	2 ft 4.5 in	.72 m	—	—
Width - stowed ⁴	2 ft 4.75 in	.73 m	2 ft 4.75 in	.73 m	2 ft 4.75 in	.73 m	—	—
max ⁴	3 ft 7.5 in	1.10 m	3 ft 7.5 in	1.10 m	3 ft 7.5 in	1.10 m	—	—
max inside	3 ft	.91 m	3 ft	.91 m	3 ft	.91 m	—	—
Weight - standard caster options	392 lbs	178 kg	411 lbs	186 kg	415 lbs	188 kg	—	—

PRODUCTIVITY								
Load height minimum	3.5 in	.09 m	3.5 in	.09 m	3.5 in	.09 m	3.5 in	.09 m
Ground clearance - center ^{1,2,3}	.75 in	.02 m	.75 in	.02 m	.75 in	.02 m	.75 in	.02 m
Average cranks - standard winch	11.5/ft	38/m	11.5/ft	38/m	11.5/ft	38/m	11.5/ft	38/m
electric winch	2 in/sec	.05 m/sec	2 in/sec	.05 m/sec	2 in/sec	.05 m/sec	2 in/sec	.05 m/sec
Fork length	1 ft 10.5 in	.57 m	1 ft 10.5 in	.57 m	1 ft 10.5 in	.57 m	1 ft 10.5 in	.57 m
Fork width	1 ft 8.5 in	.52 m	1 ft 8.5 in	.52 m	1 ft 8.5 in	.52 m	1 ft 8.5 in	.52 m
Load platform length	1 ft 11 in	.58 m	1 ft 11 in	.58 m	1 ft 11 in	.58 m	1 ft 11 in	.58 m
Load platform width	1 ft 10 in	.56 m	1 ft 10 in	.56 m	1 ft 10 in	.56 m	1 ft 10 in	.56 m
Load capacity at								
12 in (30 cm) load center	500 lbs	227 kg	400 lbs	181 kg	350 lbs	159 kg	350 lbs	159 kg

POWER	
Power source	reversible standard winch or electric winch

¹ The 10 in pneumatic rear wheel option will add 1 in (2.5 cm) to these specifications.
² The counterweight base will add 1 in (2.5 cm) to these specifications.
³ The 4-point caster option B will add 1 in (2.5 cm) to these specifications.
⁴ Outside dimensions.

Features

EASILY CONFIGURED TO MEET YOUR NEEDS

FORK OPTIONS

- Standard forks
- Load platform
- Boom

POWER OPTIONS

- Standard winch
- Electric winch

BASE OPTIONS

- Standard base (GL-4, -8 only)
- Straddle base (all units)
- Counterweight base (GL-4, -8, -10 only)

WHEEL/CASTER OPTIONS

Straddle and standard base

- 8 in (20 cm) non-marking rear wheels
- Pneumatic rear tire option
- 2 in (5 cm) dual wheel front swivel casters

Counterweight base

- 5 in (12 cm) rear swivel casters with side brakes
- 4 in (10 cm) fixed front wheels

All bases

- 4 point caster option

STANDARD FEATURES

MEASUREMENTS

GL™-4

- 5 ft 11 in (1.80 m) max lift height
- Up to 500 lb (227 kg) load capacity

GL™-8

- 10 ft .5 in (3.06 m) max lift height
- Up to 400 lb (181 kg) load capacity

GL™-10

- 11 ft 8 in (3.56 m) max lift height
- Up to 350 lb (159 kg) load capacity

GL™-12

- 13 ft 9.5 in (4.20 m) max lift height
- Up to 350 lb (159 kg) load capacity

PRODUCTIVITY

- Portable and compact design
- Lightweight durable aluminum construction
- Single door access
- Durable standard steel forks
- 8 in (20 cm) non-marking rear wheels and 2 in (5 cm) dual wheel front swivel casters (standard and straddle base only)
- 5 in (12 cm) rear swivel casters with side brakes and 4 in (10 cm) fixed front wheels (counterweight base only)
- Loads easily into a pickup truck for transporting
- Hold-down mechanism secures carriage during transport

POWER

- Standard winch
- Reversible winch handle for easy storage



OPTIONS & ACCESSORIES

PRODUCTIVITY

- Load platform
- Boom
- Aluminum ladder (standard and straddle base only)
- Pneumatic rear tires (standard and straddle base only)
- Foot-release brake (standard and straddle base only)
- Caster options
- Stair rollers (standard base only)

POWER

- Electric winch (straddle and counterweight base only)
- Winch operates while ladder is in use or stowed
- Caster option kit required for use with Straddle bases
- Electric winch option comes standard with battery and automatic charger that shuts off when fully charged.



Sky House, Daurada Drive, Stafford,
 Staffordshire, ST17 4XW, U.K.

Tel: + 44 (0) 1785 244177 Fax: + 44 (0) 1785 229874

www.skyreachaccess.com

For further information, please contact your local distributor or the Genie Industries sales office listed. Continuous improvement of our products is a Genie policy. Product specifications are subject to change without notice or obligation. The photographs and drawings in this brochure are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on the proper use of this equipment. Failure to follow the appropriate Operator's Manual when using our equipment or to otherwise act irresponsibly may result in serious injury or death. Prices and specifications subject to change without notice. The only warranty applicable is the standard written warranty applicable to the particular product and sale. Genie makes no other warranty, expressed or implied. Products and services listed may be trademarks, service marks or trade-names of TEREX Corporation and/or its subsidiaries in the USA and other countries and all rights are reserved. Copyright © 2005 Genie Industries, Inc. "Genie" is a Registered Trademark of Genie Industries, Inc. in the USA and many other countries. Genie is a TEREX Company.

GL4 3.5K 0605B Part No. 109382